RHYME®

www.rhymeaudio.com

B208

SPECIFICATION

Configuration	: 1 x 8" Bass Reflex, 2way Fullrange
Frequency Range (-10 dB)	: 55 Hz - 20 kHz
Frequency Response (±3 dB)	: 65 Hz - 20 kHz
Horizontal Coverage Angle (-6 dB)	: 90°
Vertical Coverage Angle (-6 dB)	: 60°
Crossover Modes	: Passive
System Sensitivity (1m/1w)	: 92 dB
Maximum SPL[1]	: 121 dB
System Nominal Impedance	: 8 Ohm
Power Rating (RMS / Program / Peak)[2]	: 200 / 400 / 800 Watt

Frequency Response

TRANSDUCER

HF Driver	: RM CD 340T1B08F-MK$_1$, Ferrite, 35.0 mm VC
LF Driver	: RM-8B, 8", Ferrite, 41.4mm VC

PHYSICAL

Enclosure Material	: MDF P2 15mm
Finish	: Black Texture
Input Connector	: Neutrik Speakon NL4 (x2 parallel)
Dimension (H x W x D)	: 442 x 283 x 245 mm (net) 530 x 366 x 328 mm (shipping)
Weight (Net/Shipping)	: 10 / 13 kg
Mounting Suspension	: Eye Bolt M10 Thread

Impedance

[1]Calculated based on peak power and measured sensitivity
[2]RMS: pink noise with 6dB crest factor, 12dB BW @ 60 Hz - 20000 Hz, 2Hr/step untill break, single unit

BOX

Surabaya : Jl. Margomulyo No. 5, Tandes - Surabaya, Telp. +62-81 231833504
Jakarta : Ruko Glodok Plaza Blok F no. 97
Jl. Pinangsia Raya, Mangga Besar - Jakarta Barat, Telp. +62-21 6493139

Made In Indonesia | Rev.0 (19.09.2022)